Department of Transportation Olympia, Washington 98504

June 16, 2011

ATTENTION: All Bidders and Planholders

I-90 SNOWSHED TO KEECHELUS DAM PHASE 1C-REPLACE SNOWSHED AND ADD LANES 10Y018 STATE PROJECT

Addendum No. 8

The Special Provisions for this project are amended as follows:

Special Provisions

1. On page 274, the following is added after line 39:

Finishing Equipment

Section 6-02.3(10)C is supplemented with the following:

(*****)

For the roof deck placement of Lake Keechelus Snowshed Repl. the use of hand-operated motorized power screeds and hand-operated strike-boards will be allowed.

2. On page 274, the following is added after line 47:

The roof deck on top of the WF83G Modified girders of Lake Keechelus Snowshed Repl. shall have a minimum placement thickness of six inches at the girder ends. The deck placement tolerance between the girder ends of the WF83G Modified girder line shall be + 2-inches, - ½-inch at midspan.

An acceptable roof deck surface shall be one free from deviation of more than 1 inch under the 10-foot straightedge.

The roof deck shall not be textured or combed.

3. In Appendix A, on Page 256, lines 24 through 26 are revised to read as follows:

Factory applied labels shall conform to UL 1598 <u>and Standard Specification Section 9-29</u>. Include recommended lamps and ballasts. Labels shall be located where they will be readily visible to service personnel, but not seen from normal viewing angles when lamps are in place.

4. In Appendix A, on Page 256, lines 50 through 51 are revised to read as follows:

Conform to ANSI C82.4, <u>UL 1029</u>, and <u>Standard Specification Section 9-29</u> [and <u>UL 1029</u> and capable of open-circuit operation without reduction of average lamp life]. Include the following features unless otherwise indicated:

- 5. In Appendix A, on Page 257, lines 1 through 2 are deleted.
- 6. In Appendix A, on Page 257, lines 11 through 15 are deleted.

Bidders shall furnish the Secretary of Transportation with evidence of the receipt of this addendum. This addendum will be incorporated in the contract when awarded and when formally executed.

Don Whitehouse, P.E. Regional Administrator

NOTE: COMPANY NAME MUST BE FILLED IN TO CERTIFY ACKNOWLEDGEMENT OF THIS ADDENDUM.

ADDENDUM #:		
RECEIVED BY: _		D.T.
	(Please print name)	DATE:
	(Ficase print name)	
SIGNATURE:		
001404111/		
COMPANY:		
ALL PROPOSAL	. HOLDERS PLEASE SIG	GN AND RETURN THIS PAGE BY RETURN
FAX AT 360-705-6810.		
NOTE!! SUBCONTRACTORS, MATERIALS SUPPLIERS AND PLANCENTERS		

ALL PRIME CONTRACTORS MUST ACKNOWLEDGE THIS ADDENDUM.

SNOWSHED TO KEECHELUS DAM PHASE 1C-REPLACE SNOWSHED AND ADD LANES 10Y018

NEED NOT ACKNOWLEDGE THIS ADDENDUM.